

Changes between the March 2001 draft permit and this revised draft permit have been highlighted.

United States Environmental Protection Agency
Region 10
1200 Sixth Avenue
Seattle, Washington 98101

AUTHORIZATION TO DISCHARGE UNDER THE
NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM

In compliance with the provisions of the Clean Water Act, 33 U.S.C. §1251 *et seq.*, as amended by the Water Quality Act of 1987, P.L. 100-4, the "Act",

Coeur Silver Valley, Inc.
Coeur and Galena Mines and Mills
P.O. Box 440
Wallace, Idaho 83873

is authorized to discharge from the Coeur and Galena facilities (State Industrial Codes 1044, 1021, and 1031) and Calahan and Rainbow Mine adits located near Wallace, Idaho, at the following locations:

<u>Outfall</u>	<u>Receiving Water</u>	<u>Latitude</u>	<u>Longitude</u>
001	Lake Creek	47° 29' 10"N	115° 57' 19"W
002	South Fork Coeur d'Alene River	47° 29' 52"N	115° 58' 30"W

in accordance with discharge point(s), effluent limitations, monitoring requirements and other conditions set forth herein.

This permit shall become effective

This permit and the authorization to discharge shall expire at midnight,

Signed this day of

REVISED DRAFT

Randall F. Smith
Director
Office of Water, Region 10

REVISED DRAFT

U.S. Environmental Protection Agency

REVISED DRAFT

TABLE OF CONTENTS

I.	LIMITATIONS AND MONITORING REQUIREMENTS	4
A.	Effluent Limitations and Monitoring	4
B.	Whole Effluent Toxicity Testing Requirements.	9
C.	Seepage Study	14
D.	Ambient Water Monitoring	14
E.	Quality Assurance Plan	16
II.	BEST MANAGEMENT PRACTICES PLAN	17
A.	Purpose	17
B.	Development and Implementation Schedule	17
C.	Objectives	17
D.	Elements of the BMP Plan	18
E.	Annual Review and Certification	19
F.	Documentation	20
G.	BMP Plan Modification	20
III.	MONITORING, RECORDING AND REPORTING REQUIREMENTS	20
A.	Representative Sampling (Routine and Non-Routine Discharges)	20
B.	Reporting of Monitoring Results	21
C.	Monitoring Procedures	21
D.	Additional Monitoring by Permittee	21
E.	Records Contents	21
F.	Retention of Records	22
G.	Twenty-four Hour Notice of Noncompliance Reporting	22
H.	Other Noncompliance Reporting	23
I.	Changes in Discharge of Toxic Substances	23
J.	Compliance Schedules	24
IV.	COMPLIANCE RESPONSIBILITIES	24
A.	Duty to Comply	24
B.	Penalties for Violations of Permit Conditions	24
C.	Need to Halt or Reduce Activity not a Defense	26
D.	Duty to Mitigate	26
E.	Proper Operation and Maintenance	26
F.	Bypass of Treatment Facilities	27

REVISED DRAFT

G.	Upset Conditions	28
H.	Toxic Pollutants	28
I.	Planned Changes	28
J.	Anticipated Noncompliance	29
V.	GENERAL PROVISIONS	29
A.	Permit Actions	29
B.	Duty to Reapply	29
C.	Duty to Provide Information	29
D.	Other Information	29
E.	Signatory Requirements	30
F.	Availability of Reports	31
G.	Inspection and Entry	31
H.	Property Rights	32
I.	Transfers	32
J.	State Laws	32
VI.	DEFINITIONS	32

I. LIMITATIONS AND MONITORING REQUIREMENTS

During the effective period of this permit, the permittee is authorized to discharge pollutants from outfall 001 to Lake Creek and outfall 002 to the South Fork Coeur d'Alene (SFCDA) River, within the limits and subject to the conditions set forth herein. This permit authorizes the discharge of only those pollutants resulting from facility processes, waste streams, and operations that have been clearly identified in the permit application process.

A. Effluent Limitations and Monitoring

1. The permittee must limit and monitor discharges from outfalls 001 and 002, as specified in Tables 1 and 2, below. All values represent maximum effluent limits unless otherwise indicated. The permittee must comply with the effluent limits in the tables at all times unless otherwise indicated, regardless of the frequency of monitoring or reporting required by other provisions of this permit.
2. The permittee must not discharge any floating, suspended, or submerged matter of any kind in concentrations causing a nuisance or objectionable condition or that may impair the designated beneficial uses of the receiving water.
3. The pH must not be less than 6.5 standard units (s.u.) nor greater than 9.0 s.u.
4. The permittee must collect effluent samples from the effluent stream after the last treatment unit and prior to discharge into the receiving waters.
5. Compliance Schedule for Cadmium (outfall 001 only), Lead, Mercury, and Zinc (outfall 002 only).
 - a. The permittee must comply with the maximum daily and average monthly cadmium, lead, and mercury effluent limitations in Table 1 and the maximum daily and average monthly lead, mercury, and zinc effluent limitations in Table 2 on or before **<enter date three years from effective date of the permit>**.
 - b. Until compliance with the effluent limitations is achieved, the permittee must submit an annual Report of Progress to EPA and IDEQ which outlines the progress made towards achieving compliance. The report must be submitted by January 31st of each year. At a minimum the annual report must include:

REVISED DRAFT

- i) An assessment of the previous years effluent monitoring data and comparison to the final effluent limitations.
 - ii) A report on progress made toward meeting the final effluent limitations.
 - iii) Further actions and milestones targeted for the upcoming year.
6. The permittee must collect effluent samples from the effluent stream after the last treatment unit prior to discharge into the receiving waters.
7. Method Detection Limits. For all effluent monitoring, the permittee must use methods that can achieve a method detection limit (MDL) less than the effluent limitation. Chromium VI must have an MDL of 8.0 µg/L or less.

For purposes of reporting on the discharge monitoring report (DMR), if a value is greater than the MDL, the permittee must report the actual value. If a value is less than the MDL, the permittee must report “less than {numeric MDL}” on the DMR. For purposes of calculating monthly averages, zero may be used for values less than the MDL.

Table 1 - Effluent Limitations and Monitoring Requirements for Outfall 001

Parameter	Flow Tier		Effluent Limitations				Monitoring Requirements	
			Maximum Daily		Average Monthly			
	Flow Tier Target Site	River Flow Value	µg/L	lbs/day	µg/L	lbs/day	Sample Frequency	Sample Type
Cadmium ¹	not dependent upon river flow		1.9 ^{2,4}	0.027 ^{2,4}	0.87 ^{2,4}	0.012 ^{2,4}	weekly	24-hour composite
	not dependent upon river flow		1.9 ^{4,4}	0.027 ^{4,4}	0.87 ^{4,4}	0.012 ^{4,4}		
Lead ¹	not dependent upon river flow		5.2 ^{3,4}	0.072 ^{3,4}	2.4 ^{3,4}	0.034 ^{3,4}	weekly	24-hour composite
	not dependent upon river flow		58 ^{4,4}	0.81 ^{4,4}	27 ^{4,4}	0.39 ^{4,4}		
Zinc ¹	not dependent upon river flow		114 ³	1.6 ³	51 ³	0.70 ³	weekly	24-hour composite
	not dependent upon river flow		195 ³	2.7 ³	87 ³	1.2 ³		
Copper ¹	Not dependent upon river flow		17	0.24	8.0	0.11	weekly	24-hour composite
Mercury ⁵	Lake Creek upstream of outfall 001 ⁶	<1.7 cfs	0.022 ⁴	0.00030 ⁴	0.011 ⁴	0.00015 ⁴	weekly	24-hour composite
		≥1.7 to < 3.8 cfs	0.023 ⁴	0.00032 ⁴	0.012 ⁴	0.00017 ⁴		
		>3.8 to <13.4 cfs	0.027 ⁴	0.00037 ⁴	0.014 ⁴	0.00019 ⁴		
		>13.4 to <23 cfs	0.045 ⁴	0.00062 ⁴	0.023 ⁴	0.00032 ⁴		
		≥ 23 cfs	0.064 ⁴	0.00089 ⁴	0.032 ⁴	0.00044 ⁴		
Total Suspended Solids (TSS)	--	--	30 mg/l	560 lbs/day ⁷	20 mg/l	202 lbs/day ⁷	weekly	24-hour composite
pH, s.u.	--	--	See Part I.A.3.				weekly	grab
Outfall Flow, cfs	--	--	--	--	Report in cfs	--	continuous	recording

REVISED DRAFT

Table 1 - Effluent Limitations and Monitoring Requirements for Outfall 001

Parameter	Flow Tier		Effluent Limitations				Monitoring Requirements	
			Maximum Daily		Average Monthly			
	Flow Tier Target Site	River Flow Value	µg/L	lbs/day	µg/L	lbs/day	Sample Frequency	Sample Type
E. coli, #/100 ml	--	--	Report in #/100 ml	--	--	--	monthly	grab
Chromium VI	not dependent upon river flow		--	--	Report	--	quarterly	24-hour composite
Hardness, as CaCO ₃ , mg/l	--	--	Report in mg/L	--	--	--	monthly	24-hour composite
Temperature, °C	--	--	Report in °C	--	--	--	weekly	grab
Chronic Whole Effluent Toxicity ⁸ , TU _c	--	--	Report in TU _c	--	--	--	quarterly	24-hour composite
Lake Creek upstream of outfall 001, cfs	--	--	--	--	Report in cfs	--	daily	recording

Footnotes:

- 1 These parameters must be reported and analyzed as total recoverable.
- 2 These limits will be included in the final permit if the cadmium, lead, and zinc site specific criteria for the South Fork Coeur d'Alene River are not in effect.
- 3 The limits will be included in the final permit if the cadmium, lead, and zinc site specific criteria for the South Fork Coeur d'Alene River are in effect.
- 4 **A three year compliance schedule may be included in the final permit, consistent with IDEQ's final 401 certification, to allow time to achieve these limitations.**
- 5 Mercury must be analyzed and reported as total.
- 6 The effluent limits will be determined by the average monthly average flows measured in Lake Creek upstream of outfall 001. The permittee must report the average monthly flow at this site on the DMR.
- 7 The mass-based limits (lbs/day) for TSS will only be included in the final permit if the Suspended Solids TMDL is in effect upon permit reissuance.
- 8 See Part I.B. for whole effluent toxicity testing requirements.

REVISED DRAFT

Table 2 - Effluent Limitations and Monitoring Requirements for Outfall 002								
Parameter	Flow Tier		Effluent Limitations				Monitoring Requirements	
			Maximum Daily		Average Monthly			
	Flow Tier Target Site	River Flow Value	µg/L	lbs/day	µg/L	lbs/day	Sample Frequency	Sample Type
Cadmium ¹	not dependent upon river flow		2.6 ^a	0.019 ^a	0.91 ^a	0.007 ^a	weekly	24-hour composite
	not dependent upon river flow		2.6 ^a	0.019 ^a	0.91 ^a	0.007 ^a		
Lead ¹	not dependent upon river flow		8.2 ^a	0.061 ^a	2.9 ^a	0.022 ^a	weekly	24-hour composite
	not dependent upon river flow		88 ^a	0.66 ^a	32 ^a	0.24 ^a		

REVISED DRAFT

Table 2 - Effluent Limitations and Monitoring Requirements for Outfall 002								
Parameter	Flow Tier		Effluent Limitations				Monitoring Requirements	
			Maximum Daily		Average Monthly			
	Flow Tier Target Site	River Flow Value	µg/L	lbs/day	µg/L	lbs/day	Sample Frequency	Sample Type
Zinc ¹	not dependent upon river flow		146 ^{2A}	1.1 ^{2A}	53 ^{2A}	0.39 ^{2A}	weekly	24-hour composite
	not dependent upon river flow		237 ^{2A}	1.8 ^{2A}	85 ^{2A}	0.63 ^{2A}		
Copper ¹	SFCDA River directly upstream of the outfall ⁶	< 48 cfs	63	0.47	29	0.22	weekly	24-hour composite
		≥ 48 to < 109 cfs	70	0.52	32	0.24		
		≥ 109 to < 379 cfs	107	0.80	50	0.37		
		≥ 379 to < 649 cfs	217	1.6	101	0.75		
		≥ 649 cfs	179	1.3	83	0.62		
Mercury ⁵	SFCDA River directly upstream of the outfall ⁶	< 48 cfs	0.13 ⁴	0.00097 ⁴	0.065 ⁴	0.00049 ⁴	weekly	24-hour composite
		≥ 48 to < 109 cfs	0.19 ⁴	0.0014 ⁴	0.095 ⁴	0.00071 ⁴		
		≥109 to < 379 cfs	0.41 ⁴	0.0031 ⁴	0.20 ⁴	0.0015 ⁴		
		≥379 to < 649 cfs	1.4 ⁴	0.010 ⁴	0.68 ⁴	0.0051 ⁴		
		≥ 649 cfs	2.3 ⁴	0.017 ⁴	1.2 ⁴	0.0090 ⁴		
Total Suspended Solids	--	--	30 mg/L	248 lbs/day ⁷	20 mg/L	80 lbs/day ⁷	weekly	24-hour composite
pH, s.u.	--	--	See Part I.A.3.				weekly	grab
Outfall Flow, cfs	--	--	--	--	Report in cfs	--	continuous	recording
E. coli, #/100 ml	--	--	Report in #/100 ml	--	--	--	monthly	grab
Hardness, as CaCO ₃ , mg/L	--	--	Report in mg/L	--	--	--	monthly	24-hour composite

REVISED DRAFT

Table 2 - Effluent Limitations and Monitoring Requirements for Outfall 002								
Parameter	Flow Tier		Effluent Limitations				Monitoring Requirements	
			Maximum Daily		Average Monthly			
	Flow Tier Target Site	River Flow Value	µg/L	lbs/day	µg/L	lbs/day	Sample Frequency	Sample Type
Temperature, °C	--	--	Report in °C	--	--	--	weekly	grab
Chronic Whole Effluent Toxicity ⁸ , TU _c	--	--	Report in TU _c	--	--	--	quarterly	24-hour composite
SFCDA River upstream of outfall 002, cfs	--	--	--	--	Report in cfs	--	daily	recording
Footnotes:								
1	These parameters must be reported and analyzed as total recoverable.							
2	These limits will be included in the final permit if the cadmium, lead, and zinc site specific criteria for the South Fork Coeur d’Alene River are not in effect.							
3	The limits will be included in the final permit if the cadmium, lead, and zinc site specific criteria for the South Fork Coeur d’Alene River are in effect.							
4	A compliance schedule may be included in the final permit, consistent with IDEQ’s final 401 certification, to allow time to achieve these limitations.							
5	Mercury must be analyzed and reported as total.							
6	The effluent limits will be determined by the average monthly flow s in the South Fork Coeur d’Alene River upstream of outfall 002. The permittee must report the average monthly flow at this site on the DMR.							
7	The mass-based limits (lbs/day) for TSS will only be included in the final permit if the Suspended Solids TMDL is in effect upon permit reissuance.							
8	See Part I.B. for whole effluent toxicity testing requirements.							

B. Whole Effluent Toxicity Testing Requirements. The permittee must conduct chronic toxicity tests on effluent samples from outfalls 001 and 002. Testing must be conducted in accordance with subsections 1 through 6, below.

1. Test Species and Methods

- a. Tests must be run four times per year, during the months of February, May, August, and November.

REVISED DRAFT

- b. Toxicity testing must be conducted on 24-hour composite samples of effluent. In addition, a split of each sample collected must be analyzed for the chemical and physical parameters required in Part I.A above. When the timing of sample collection coincides with that of the sampling required in Part I.A, analysis of the split sample will fulfill the requirements of Part I.A. as well.
 - c. The permittee must conduct tests with the water flea, *Ceriodaphnia dubia* (survival and reproduction test) and the fathead minnow, *Pimephales promelas* (larval survival and growth test) for the first three suites of tests. After this screening period, monitoring shall be conducted using the most sensitive species.
 - d. The presence of chronic toxicity must be determined as specified in *Short-Term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms*, Third Edition, EPA/600-4-91-002, July 1994.
 - e. Results must be reported in TU_c (chronic toxic units), where $TU_c = 100/IC_{25}$. See Part VI. for a definition of IC_{25} .
2. Toxicity Triggers. For the purposes of determining compliance with paragraphs I.B.4. and I.B.5., the chronic toxicity trigger is defined as toxicity exceeding the trigger values in Table 3.

Table 3 - Chronic Toxicity Triggers and Receiving Water Concentrations			
Outfall	Flow Tier (based on flow directly upstream of the outfall)	Chronic Toxicity Trigger¹, TU_c	Receiving Water Concentration, % effluent
001	< 1.7 cfs	1.1	90
	≥ 1.7 to < 3.8 cfs	1.2	86
	≥ 3.8 to < 13.4 cfs	1.4	73
	≥ 13.4 to < 23 cfs	2.3	43
	≥ 23 cfs	3.2	31
002	< 48 cfs	6.6	15
	≥ 48 to < 109 cfs	9.6	10

REVISED DRAFT

	≥ 109 to < 379 cfs	21	5
	≥ 379 to < 649 cfs	69	1.4
	≥ 649 cfs	120	0.9
Footnote: 1 The trigger value shall be determined by using the average monthly flow at the flow tier station (upstream of outfalls 001 and 002).			

3. Quality Assurance

- a. The toxicity testing on each organism must include a series of five test dilutions and a control. The series must include: the receiving water concentration (RWC), which is the dilution associated with the chronic toxicity trigger; two dilutions above the RWC, and; two dilutions below the RWC. The RWCs for each outfall are provided in Table 3, above.
- b. All quality assurance criteria and statistical analyses used for chronic tests and reference toxicant tests must be in accordance with *Short-Term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms*, Third Edition, EPA/600-4-91-002, July 1994, and individual test protocols.
- c. In addition to those quality assurance measures specified in the methodology, the following quality assurance procedures must be followed:
 - i) If organisms are not cultured in-house, concurrent testing with reference toxicants must be conducted. If organisms are cultured in-house, monthly reference toxicant testing is sufficient. Reference toxicant tests must be conducted using the same test conditions as the effluent toxicity tests.
 - ii) If either of the reference toxicant tests or the effluent tests do not meet all test acceptability criteria as specified in the test methods manual, the permittee must re-sample and re-test within 14 days of receipt of the test results.

REVISED DRAFT

- iii) Control and dilution water must be receiving water or lab water, as appropriate, as described in the manual. If the dilution water used is different from the culture water, a second control, using culture water must also be used. Receiving water may be used as control and dilution water upon notification of the Environmental Protection Agency (EPA). In no case shall water that has not met test acceptability criteria be used for either dilution or control.

4. Accelerated Testing

- a. If chronic toxicity is detected above a trigger specified in paragraph B.2., the permittee must conduct six more tests, bi-weekly, over a twelve week period. This accelerated testing must be initiated within **two weeks** of receipt of the test results that indicate an exceedence. Part I.B.4.d., below, allows for the permittee to conduct only one accelerated test if the conditions under that part are met.
- b. If none of the six accelerated tests exceed the trigger, then the permittee may return to the normal testing frequency.
- c. If any of the six tests exceed the trigger, then the permittee shall initiate a toxicity reduction evaluation (TRE) in accordance with Part I.B.5.
- d. Initial Investigation. If the permittee demonstrates through an evaluation of facility operations that the cause of the exceedence is known and corrective actions have been implemented, only one accelerated test is necessary. If toxicity exceeding the trigger is detected in this test, then the TRE requirements in Part I.B.5. shall apply. If toxicity does not exceed the trigger, then the permittee may return to the normal quarterly testing frequency.

5. Toxicity Reduction Evaluation and Toxicity Identification Evaluation

- a. If a toxicity trigger is exceeded during accelerated testing under Part I.B.4.c. or d., the permittee must initiate a TRE in accordance with *Generalized Methodology for Conducting Industrial Toxicity Reduction Evaluations* (EPA/600/2-88/070) **within fifteen (15) days** of the exceedence. The TRE must include:
 - i) further actions to investigate and identify the cause of toxicity;
 - ii) actions the permittee will take to mitigate the impact of the discharge and to prevent the recurrence of toxicity; and
 - iii) a schedule for these actions.

REVISED DRAFT

- b. If a TRE is initiated prior to completion of the accelerated testing, the accelerated testing schedule may be terminated, or used as necessary in performing the TRE.
- c. The permittee may initiate a Toxicity Identification Evaluation (TIE) as part of the TRE process. Any TIE must be performed in accordance with EPA guidance manuals, *Toxicity Identification Evaluation; Characterization of Chronically Toxic Effluents, Phase I* (EPA/600/6-91/005F), *Methods for Aquatic Toxicity Identification Evaluations, Phase II: Toxicity Identification Procedures for Samples Exhibiting Acute and Chronic Toxicity* (EPA/600/R-92/080), and *Methods for Aquatic Toxicity Identification Evaluations, Phase III: Toxicity Confirmation Procedures for Samples Exhibiting Acute and Chronic Toxicity* (EPA-600/R-92/081).

6. Reporting

- a. The permittee must submit a full report of the results of the toxicity tests with the DMR for the month following sample collection.
- b. The permittee must submit the results of any accelerated testing, under Part I.B.4., within **two weeks** of receipt of the results from the lab. The full report must be submitted within **four weeks** of receipt of the results from the lab. If an initial investigation, under Part I.B.4.d. indicates the source of toxicity and accelerated testing is unnecessary, the result of the investigation must be submitted with the full report.
- c. The report of toxicity test results must include all relevant information outlined in Section 10, Report Preparation, of *Short-Term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms*, Third Edition, EPA/600-4-91-002, July 1994. The full report must include: toxicity test results, dates of sample collection and initiation of each test, the toxicity triggers as defined in paragraph B.2., flow rate at the time of sample collection, and the results of the monitoring required in Part I.A.

- C. Seepage Study.** The permittee must conduct a seepage study to determine if there are unmonitored discharges of pollutants from the Lake Creek settling ponds and Osburn tailings ponds into Lake Creek or the SFCDA River.
1. The permittee must quantify seepage by performing a water balance analysis for each pond based on monitoring and evaluation of inflows, outflow, and estimated losses (i.e., evaporation). Seasonal variation must be addressed in each water balance analysis.
 2. Results of the seepage study must be submitted to EPA and IDEQ in a Seepage Study Report. The report must include a description of the methodology and data used to determine if seepage is occurring and the results of the study. The Seepage Study Report for Lake Creek settling ponds and Osburn tailings ponds must be submitted to EPA by **<enter date 18 months from the effective date of this permit>**.
- D. Ambient Water Monitoring.** The permittee must perform the following ambient water monitoring program.
1. Water Quality Monitoring
 - a. The permittee must monitor Lake Creek directly upstream of outfall 001 and the South Fork Coeur d'Alene River directly upstream of outfall 002.
 - b. All locations must be monitored four times per year (i.e., quarterly) during February, May, August, and November.
 - c. All ambient samples must be depth-integrated samples.
 - d. Samples must be analyzed for the parameters listed in Table 4 to achieve MDLs that are equivalent to or less than those listed in Table 4. The permittee may request different MDLs. Such a request must be in writing and must be approved by EPA.

Table 4: Ambient Water Monitoring		
Parameter	Units	Method Detection Limit
Copper, dissolved	µg/L	1
Mercury, total	µg/L	0.001
pH	standard units	--
Temperature	°C	--
Hardness (as CaCO ₃) ¹	mg/l	--
Footnote:		
1 Hardness shall be monitored upstream and downstream of the outfall.		

2. River Flow Monitoring

Daily streamflow must be monitored for Lake Creek directly upstream of outfall 001 according to Section I.A (Table 1) and the South Fork Coeur d'Alene River directly upstream of outfall 002 according to Section I.A. (Table 2).

3. **Bioassessment Monitoring**

Annual instream bioassessment monitoring shall be conducted directly downstream of outfall 001 and outfall 002. Bioassessment monitoring shall be consistent with the most recent Idaho Department of Environmental Quality Beneficial Use Reconnaissance Project workplan for wadeable streams.

4. Quality assurance/quality control plans for all the monitoring must be documented in the Quality Assurance Plan required under Part I.E.
5. The permittee must submit an annual report summarizing the results of the ambient water monitoring to EPA and IDEQ by **January 31st** of the following year. At a minimum, the report must include: the sample locations; dates of sample collection and analyses; analytical results; a discussion of sampling and laboratory methods, including quality assurance/quality control; and, data handling.

REVISED DRAFT

E. Quality Assurance Plan. The permittee must develop a quality assurance plan (QAP) for all monitoring required by this permit. The plan must be submitted to EPA and Idaho Department of Environmental Quality (IDEQ) for review by **<enter date 60 days from the effective date of this permit>** and implemented by **<enter date 120 days from the effective date of this permit>**. Any existing QAPs may be modified for submittal under this section.

1. The QAP must be designed to assist in planning for the collection and analysis of effluent and receiving water samples in support of the permit and in explaining data anomalies when they occur.
2. Throughout all sample collection and analysis activities, the permittee must use the EPA-approved QA/QC and chain-of-custody procedures described in *Requirements for Quality Assurance Project Plans* (EPA/QA/R-5) and *Guidance for Quality Assurance Project Plans* (EPA/QA/G-5). The QAP must be prepared in the format which is specified in these documents.
3. At a minimum, the QAP must include the following:
 - a. Details on the number of samples, type of sample containers, preservation of samples, holding times, analytical methods, analytical detection and quantitation limits for each target compound, type and number of quality assurance field samples, precision and accuracy requirements, sample preparation requirements, sample shipping methods, and laboratory data delivery requirements.
 - b. Map(s) indicating the location of each sampling point.
 - c. Qualification and training of personnel.
 - d. Name(s), address(es) and telephone number(s) of the laboratories, used by or proposed to be used by the permittee.
4. The permittee must amend the QAP whenever there is a modification in sample collection, sample analysis, or other procedure addressed by the QAP.
5. Copies of the QAP must be kept on site and made available to EPA and/or IDEQ upon request.

REVISED DRAFT

II. BEST MANAGEMENT PRACTICES PLAN

- A. **Purpose.** Through implementation of the best management practices (BMP) plan the permittee must prevent or minimize the generation and the potential for the release of pollutants from the facility to the waters of the United States.
- B. **Development and Implementation Schedule.** The permittee must develop and implement a BMP Plan which achieves the objectives and the specific requirements listed below. A copy of the BMP Plan must be submitted to EPA by **<enter date 120 days from the effective date of the permit>**. Any existing BMP plans may be modified for submittal under this section. The permittee must implement the provisions of the plan as conditions of this permit by **<enter date 180 days from the effective date of this permit>**.
- C. **Objectives.** The permittee must develop and amend the BMP Plan consistent with the following objectives for the control of pollutants.
1. The number and quantity of pollutants and the toxicity of effluent generated, discharged or potentially discharges at the facility must be minimized by the permittee to the extent feasible by managing each waste stream in the most appropriate manner.
 2. Under the BMP Plan and any Standard Operating Procedures included in the BMP Plan, the permittee must ensure proper operation and maintenance of water management and wastewater treatment systems. BMP Plan elements must be developed in accordance with good engineering practices.
 3. Each facility component or system must be examined for its waste minimization opportunities and its potential for causing a release of significant amounts of pollutants to waters of the United States due to equipment failure, improper operation, natural phenomena such as rain or snowfall, etc. The examination must include all normal operations and ancillary activities including material storage areas, storm water, in-plant transfer, material handling and process handling areas, loading or unloading operations, spillage or leaks, sludge and waste disposal, or drainage from raw material storage.
- D. **Elements of the BMP Plan.** The BMP Plan must be consistent with the objectives above and the general guidance contained in *Guidance Manual for Developing Best Management Practices* (EPA 833-B-93-004, October 1993) or any subsequent

REVISED DRAFT

revisions to this guidance document. The BMP Plan must include, at a minimum, the following items:

1. **Statement of BMP policy.** The BMP Plan must include a statement of management commitment to provide the necessary financial, staff, equipment, and training resources to develop and implement the BMP Plan on a continuing basis.
2. **Structure, functions, and procedures of the BMP Committee.** The BMP Plan must establish a BMP Committee responsible for developing, implementing, and maintaining the BMP Plan.
3. **Release Identification and Assessment.** A release identification is the systematic cataloging of areas at a facility with ongoing or potential releases to the environment. A release assessment is used to determine the impact on human health and the environment of any on-going or potential release identified. The identification and assessment process involves the evaluation of both current discharges and potential discharges.
4. **Measures and Controls.** The permittee must develop a description of pollution prevention controls, BMPs, and other measures appropriate for the facility, and implement such controls. The appropriateness and priorities of controls in the BMP Plan must reflect identified potential sources of pollutants at the facility. The description of management controls must address the following minimum components:
 - a. **Good Housekeeping.** A program by which the facility is kept in a clean and orderly fashion to prevent releases to the environment.
 - b. **Preventative Maintenance.** A program focused on preventing releases caused by equipment problems, rather than repair of equipment after problems occur.
 - c. **Inspections.** A program established to oversee facility operations and identify actual or potential environmental releases and to ensure that BMPs are being implemented.
 - d. **Security.** A program designed to avoid releases due to accidental or intentional entry.

REVISED DRAFT

- e. Employee Training. A program developed to instill in employees an understanding of the BMP Plan.
 - f. Recordkeeping and Reporting. A program designed to maintain relevant information and foster communication.
5. Specific Best Management Practices. The BMP Plan must establish specific BMPs or other measures which ensure that the following specific requirements are met:
- a. Solids, sludges, or other pollutants removed in the course of treatment or control of water and wastewaters must be disposed of in a manner such as to prevent any pollutant from such materials from entering navigable waters.
 - b. Ensure proper management of solid and hazardous waste in accordance with regulations promulgated under the Resource Conservation and Recovery Act (RCRA). Management practices required under RCRA regulations must be referenced in the BMP Plan.
 - c. Ensure proper management of materials in accordance with Spill Prevention, Control, and Countermeasure (SPCC) plans under Section 311 of the Act and 40 CFR Part 112. The BMP Plan may incorporate any part of such plans into the BMP Plan by reference.

E. Annual Review and Certification.

- 1. Annual Review. An annual review of the BMP Plan must be conducted by the responsible manager and BMP committee.
- 2. Annual Certification. The permittee must prepare a certified statement that the above reviews have been completed and that the BMP Plan fulfills the requirements set forth in the permit. This statement must be signed in accordance with Part V.E. (Signatory Requirements) of this permit. This statement must be submitted to EPA on or before **January 31st** of each year of operation under this permit after the initial BMP submittal.

REVISED DRAFT

F. Documentation. The permittee must maintain a copy of the BMP Plan at the facility and make it available to EPA or an authorized representative upon request.

G. BMP Plan Modification.

1. The permittee must amend the BMP Plan whenever there is a change in the facility or in the operation of the facility which materially increases the generation of pollutants or their release or potential release to surface waters.
2. The permittee must amend the BMP Plan whenever it is found to be ineffective in achieving the general objective of preventing and minimizing the generation and the potential for the release of pollutants from the facility to the waters of the United States and/or the specific requirements above.
3. Any changes to the BMP Plan must be consistent with the objectives and specific requirements listed above. All changes in the BMP Plan must be reported to EPA in writing.

III. MONITORING, RECORDING AND REPORTING REQUIREMENTS

A. Representative Sampling (Routine and Non-Routine Discharges). Samples and measurements must be representative of the volume and nature of the monitored discharge.

In order to ensure that the effluent limits set forth in this permit are not violated at times other than when routine samples are taken, the permittee must collect additional samples at the appropriate outfall whenever any discharge occurs that may reasonably be expected to cause or contribute to a violation that is unlikely to be detected by a routine sample. The permittee must analyze the additional samples for those parameters limited in Part I.A. of this permit that are likely to be affected by the discharge.

The permittee must collect such additional samples as soon as the spill, discharge, or bypassed effluent reaches the outfall. The samples must be analyzed in accordance with paragraph III.C (“Monitoring Procedures”). The permittee must report all additional monitoring in accordance with paragraph III.D (“Additional Monitoring by Permittee”).

- B. Reporting of Monitoring Results.** The permittee must summarize monitoring results each month on the DMR form (EPA No. 3320-1) or equivalent. The permittee must submit reports monthly, postmarked by the **10th day of the following month**. The permittee must sign and certify all DMRs, and all other reports, in accordance with the requirements of Part V.E. of this permit ("Signatory Requirements"). The permittee must submit the legible originals of these documents to the Director, Office of Water, with copies to IDEQ at the following addresses:

United States Environmental Protection Agency
Region 10
1200 Sixth Avenue, OW-133
Seattle, Washington 98101

Idaho Department of Environmental Quality
Coeur d'Alene Regional Office
2110 Ironwood Parkway
Coeur d'Alene, Idaho 83814

- C. Monitoring Procedures.** Monitoring must be conducted according to test procedures approved under 40 CFR 136, unless other test procedures have been specified in this permit.
- D. Additional Monitoring by Permittee.** If the permittee monitors any pollutant more frequently than required by this permit, using test procedures approved under 40 CFR 136 or as specified in this permit, the permittee must include the results of this monitoring in the calculation and reporting of the data submitted in the DMR.

Upon request by the Director, the permittee must submit results of any other sampling, regardless of the test method used.

- E. Records Contents.** Records of monitoring information must include:

1. the date, exact place, and time of sampling or measurements;
2. the name(s) of the individual(s) who performed the sampling or measurements;
3. the date(s) analyses were performed;
4. the name(s) of the individual(s) who performed the analyses;
5. the analytical techniques or methods used; and
6. the results of such analyses.

REVISED DRAFT

F. Retention of Records. The permittee must retain records of all monitoring information, including, all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, copies of DMRs, a copy of the NPDES permit, and records of all data used to complete the application for this permit, for a period of at least **five years** from the date of the sample, measurement, report or application. This period may be extended by request of the Director or IDEQ at any time.

G. Twenty-four Hour Notice of Noncompliance Reporting

1. The permittee must report the following occurrences of noncompliance by telephone within 24 hours from the time the permittee becomes aware of the circumstances:
 - a. any noncompliance that may endanger health or the environment;
 - b. any unanticipated bypass that exceeds any effluent limitation in the permit (See Part IV.F., "Bypass of Treatment Facilities");
 - c. any upset that exceeds any effluent limitation in the permit (See Part IV.G., "Upset Conditions"); or
 - d. any violation of a maximum daily discharge limitation for any of the pollutants listed in the permit.
2. The permittee must also provide a written submission within **five days** of the time that the permittee becomes aware of any event required to be reported under subpart 1 above. The written submission must contain:
 - a. a description of the noncompliance and its cause;
 - b. the period of noncompliance, including exact dates and times;
 - c. the estimated time noncompliance is expected to continue if it has not been corrected; and
 - d. steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.

REVISED DRAFT

3. The Director may waive the written report on a case-by-case basis if the oral report has been received within 24 hours by the NPDES Compliance Hotline in Seattle, Washington, by telephone, (206) 553-1846.
4. Reports must be submitted to the addresses in Part III.B ("Reporting of Monitoring Results").

H. Other Noncompliance Reporting. The permittee must report all instances of noncompliance, not required to be reported within 24 hours, at the time that monitoring reports for Part III.B ("Reporting of Monitoring Results") are submitted. The reports must contain the information listed in Part III.G.2 of this permit ("Twenty-four Hour Notice of Noncompliance Reporting").

I. Changes in Discharge of Toxic Substances. The permittee must notify the Director and IDEQ as soon as it knows, or has reason to believe:

1. That any activity has occurred or will occur that would result in the discharge, on a routine or frequent basis, of any toxic pollutant that is not limited in the permit, if that discharge may reasonably be expected to exceed the highest of the following "notification levels":
 - a. One hundred micrograms per liter (100 µg/L);
 - b. Two hundred micrograms per liter (200 µg/L) for acrolein and acrylonitrile; five hundred micrograms per liter (500 µg/L) for 2,4-dinitrophenol and for 2-methyl-4, 6-dinitrophenol; and one milligram per liter (1 mg/l) for antimony;
 - c. Five (5) times the maximum concentration value reported for that pollutant in the permit application in accordance with 40 CFR 122.21(g)(7); or
 - d. The level established by the Director in accordance with 40 CFR 122.44(f).
2. That any activity has occurred or will occur that would result in any discharge, on a non-routine or infrequent basis, of any toxic pollutant that is not limited in the permit, if that discharge may reasonably be expected to exceed the highest of the following "notification levels":

REVISED DRAFT

- a. Five hundred micrograms per liter (500 µg/L);
- b. One milligram per liter (1 mg/l) for antimony;
- c. Ten (10) times the maximum concentration value reported for that pollutant in the permit application in accordance with 40 CFR 122.21(g)(7); or
- d. The level established by the Director in accordance with 40 CFR 122.44(f).

J. Compliance Schedules. Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit must be submitted no later than 14 days following each schedule date.

IV. COMPLIANCE RESPONSIBILITIES

A. Duty to Comply. The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action, for permit termination, revocation and reissuance, or modification, or for denial of a permit renewal application.

B. Penalties for Violations of Permit Conditions

1. **Civil Penalties.** Pursuant to 40 CFR 19 and the Act, any person who violates section 301, 302, 306, 307, 308, 318 or 405 of the Act, or any permit condition or limitation implementing any such sections in a permit issued under section 402, or any requirement imposed in a pretreatment program approved under sections 402(a)(3) or 402(b)(8) of the Act, is subject to a civil penalty not to exceed the maximum amounts authorized by Section 309(d) of the Act and the Federal Civil Penalties Inflation Adjustment Act (28 U.S.C. § 2461 note) as amended by the Debt Collection Improvement Act (31 U.S.C. § 3701 note) (currently \$31,500 per day for each violation).
2. **Administrative Penalties.** Any person may be assessed an administrative penalty by the Administrator for violating section 301, 302, 306, 307, 308, 318

REVISED DRAFT

or 405 of this Act, or any permit condition or limitation implementing any of such sections in a permit issued under section 402 of this Act. Pursuant to 40 CFR 19 and the Act, administrative penalties for Class I violations are not to exceed the maximum amounts authorized by Section 309(g)(2)(A) of the Act and the Federal Civil Penalties Inflation Adjustment Act (28 U.S.C. § 2461 note) as amended by the Debt Collection Improvement Act (31 U.S.C. § 3701 note) (currently \$11,000 per violation, with the maximum amount of any Class I penalty assessed not to exceed \$27,500). Pursuant to 40 CFR 19 and the Act, penalties for Class II violations are not to exceed the maximum amounts authorized by Section 309(g)(2)(B) of the Act and the Federal Civil Penalties Inflation Adjustment Act (28 U.S.C. § 2461 note) as amended by the Debt Collection Improvement Act (31 U.S.C. § 3701 note) (currently \$11,000 per day for each day during which the violation continues, with the maximum amount of any Class II penalty not to exceed \$137,500).

3. Criminal Penalties:

- a. Negligent Violations. The Act provides that any person who negligently violates sections 301, 302, 306, 307, 308, 318, or 405 of the Act, or any condition or limitation implementing any of such sections in a permit issued under section 402 of the Act, or any requirement imposed in a pretreatment program approved under section 402(a)(3) or 402(b)(8) of the Act, is subject to criminal penalties of \$2,500 to \$25,000 per day of violation, or imprisonment of not more than 1 year, or both. In the case of a second or subsequent conviction for a negligent violation, a person shall be subject to criminal penalties of not more than \$50,000 per day of violation, or by imprisonment of not more than 2 years, or both.
- b. Knowing Violations. Any person who knowingly violates such sections, or such conditions or limitations is subject to criminal penalties of \$5,000 to \$50,000 per day of violation, or imprisonment for not more than 3 years, or both. In the case of a second or subsequent conviction for a knowing violation, a person shall be subject to criminal penalties of not more than \$100,000 per day of violation, or imprisonment of not more than 6 years, or both.
- c. Knowing Endangerment. Any person who knowingly violates section 301, 302, 303, 306, 307, 308, 318 or 405 of the Act, or any permit

REVISED DRAFT

condition or limitation implementing any of such sections in a permit issued under section 402 of the Act, and who knows at that time that he thereby places another person in imminent danger of death or serious bodily injury, shall, upon conviction, be subject to a fine of not more than \$250,000 or imprisonment of not more than 15 years, or both. In the case of a second or subsequent conviction for a knowing endangerment violation, a person shall be subject to a fine of not more than \$500,000 or by imprisonment of not more than 30 years, or both. An organization, as defined in section 309(c)(3)(B)(iii) of the Act, shall, upon conviction of violating the imminent danger provision, be subject to a fine of not more than \$1,000,000 and can be fined up to \$2,000,000 for second or subsequent convictions.

- d. **False Statements.** The Act provides that any person who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than \$10,000, or by imprisonment for not more than 2 years, or both. If a conviction of a person is for a violation committed after a first conviction of such person under this paragraph, punishment is a fine of not more than \$20,000 per day of violation, or by imprisonment of not more than 4 years, or both. The Act further provides that any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or non-compliance shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than 6 months per violation, or by both.

- C. **Need to Halt or Reduce Activity not a Defense.** It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with this permit.
- D. **Duty to Mitigate.** The permittee must take all reasonable steps to minimize or prevent any discharge in violation of this permit that has a reasonable likelihood of adversely affecting human health or the environment.
- E. **Proper Operation and Maintenance.** The permittee must at all times properly operate and maintain all facilities and systems of treatment and control (and related

REVISED DRAFT

appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls and appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by the permittee only when the operation is necessary to achieve compliance with the conditions of the permit.

F. Bypass of Treatment Facilities

1. Bypass not exceeding limitations. The permittee may allow any bypass to occur that does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of paragraphs 2 and 3 of this Part.
2. Notice.
 - a. Anticipated bypass. If the permittee knows in advance of the need for a bypass, it must submit prior notice, if possible at least 10 days before the date of the bypass.
 - b. Unanticipated bypass. The permittee must submit notice of an unanticipated bypass as required under Part III.G ("Twenty-four Hour Notice of Noncompliance Reporting").
3. Prohibition of bypass.
 - a. Bypass is prohibited, and the Director or IDEQ may take enforcement action against the permittee for a bypass, unless:
 - i) The bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
 - ii) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass that

REVISED DRAFT

occurred during normal periods of equipment downtime or preventive maintenance; and

iii) The permittee submitted notices as required under paragraph 2 of this Part.

b. The Director may approve an anticipated bypass, after considering its adverse effects, if the Director determine that it will meet the three conditions listed above in paragraph 3.a. of this Part.

G. Upset Conditions

1. Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with such technology-based permit effluent limitations if the permittee meets the requirements of paragraph 2 of this Part. No determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review.

2. Conditions necessary for a demonstration of upset. To establish the affirmative defense of upset, the permittee must demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:

a. An upset occurred and that the permittee can identify the cause(s) of the upset;

b. The permitted facility was at the time being properly operated;

c. The permittee submitted notice of the upset as required under Part III.G, “Twenty-four Hour Notice of Noncompliance Reporting;” and

d. The permittee complied with any remedial measures required under Part IV.D, “Duty to Mitigate.”

3. Burden of proof. In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.

H. Toxic Pollutants. The permittee must comply with effluent standards or prohibitions established under Section 307(a) of the Act for toxic pollutants within the time provided

REVISED DRAFT

in the regulations that establish those standards or prohibitions, even if the permit has not yet been modified to incorporate the requirement.

I. Planned Changes. The permittee must give notice to the Director and IDEQ as soon as possible of any planned physical alterations or additions to the permitted facility whenever:

1. The alteration or addition to a permitted facility may meet one of the criteria for determining whether a facility is a new source as determined in 40 CFR 122.29(b); or
2. The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants that are subject neither to effluent limitations in the permit, nor to notification requirements under Part III.I (“Changes in Discharge of Toxic Substances”).

J. Anticipated Noncompliance. The permittee must give advance notice to the Director and IDEQ of any planned changes in the permitted facility or activity that may result in noncompliance with this permit.

V. GENERAL PROVISIONS

A. Permit Actions. This permit may be modified, revoked and reissued, or terminated for cause as specified in 40 CFR 122.62, 122.64, or 124.5. The filing of a request by the permittee for a permit modification, revocation and reissuance, termination, or a notification of planned changes or anticipated noncompliance, does not stay any permit condition.

B. Duty to Reapply. If the permittee intends to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for and obtain a new permit. In accordance with 40 CFR 122.21(d), and unless permission for the application to be submitted at a later date has been granted by the Regional Administrator, the permittee must submit a new application at least **180 days before the expiration date of this permit.**

C. Duty to Provide Information. The permittee must furnish to the Director and IDEQ, within the time specified in the request, any information that the Director or IDEQ may request to determine whether cause exists for modifying, revoking and reissuing, or

REVISED DRAFT

terminating this permit, or to determine compliance with this permit. The permittee must also furnish to the Director or IDEQ, upon request, copies of records required to be kept by this permit.

D. Other Information. When the permittee becomes aware that it failed to submit any relevant facts in a permit application, or that it submitted incorrect information in a permit application or any report to the Director or IDEQ, it must promptly submit the omitted facts or corrected information.

E. Signatory Requirements. All applications, reports or information submitted to the Director and IDEQ must be signed and certified as follows.

1. All permit applications must be signed as follows:
 - a. For a corporation: by a responsible corporate officer.
 - b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively.
 - c. For a municipality, state, federal, or other public agency: by either a principal executive officer or ranking elected official.
2. All reports required by the permit and other information requested by the Director or IDEQ must be signed by a person described above or by a duly authorized representative of that person. A person is a duly authorized representative only if:
 - a. The authorization is made in writing by a person described above;
 - b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company; and
 - c. The written authorization is submitted to the Director and IDEQ.

REVISED DRAFT

3. Changes to authorization. If an authorization under Part V.E.2 is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part V.E.2. must be submitted to the Director and IDEQ prior to or together with any reports, information, or applications to be signed by an authorized representative.
4. Certification. Any person signing a document under this Part must make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

- F. **Availability of Reports.** In accordance with 40 CFR 2, information submitted to EPA pursuant to this permit may be claimed as confidential by the permittee. In accordance with the Act, permit applications, permits and effluent data are not considered confidential. Any confidentiality claim must be asserted at the time of submission by stamping the words "confidential business information" on each page containing such information. If no claim is made at the time of submission, EPA may make the information available to the public without further notice to the permittee. If a claim is asserted, the information will be treated in accordance with the procedures in 40 CFR 2, Subpart B (Public Information) and 41 Fed. Reg. 36902 through 36924 (September 1, 1976), as amended.
- G. **Inspection and Entry.** The permittee must allow the Director, IDEQ, or an authorized representative (including an authorized contractor acting as a representative of the Administrator), upon the presentation of credentials and other documents as may be required by law, to:

REVISED DRAFT

1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
4. Sample or monitor at reasonable times, for the purpose of assuring permit compliance or as otherwise authorized by the Act, any substances or parameters at any location.

H. Property Rights. The issuance of this permit does not convey any property rights of any sort, or any exclusive privileges, nor does it authorize any injury to persons or property or invasion of other private rights, nor any infringement of state or local laws or regulations.

I. Transfers. This permit is not transferable to any person except after notice to the Director. The Director may require modification or revocation and reissuance of the permit to change the name of the permittee and incorporate such other requirements as may be necessary under the Act. (See 40 CFR 122.61; in some cases, modification or revocation and reissuance is mandatory).

J. State Laws. Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable state law or regulation under authority preserved by Section 510 of the Act.

VI. DEFINITIONS

1. “Act” means the Clean Water Act.
2. “Administrator” means the Administrator of the EPA, or an authorized representative.

REVISED DRAFT

3. “Average monthly discharge limitation” means the highest allowable average of “daily discharges” over a calendar month, calculated as the sum of all “daily discharges” measured during a calendar month divided by the number of “daily discharges” measured during that month.
4. “Best Management Practices” (BMPs) means schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the United States. BMPs also include treatment requirements, operating procedures, and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage.
5. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility.
6. “CWA” means the Clean Water Act.
7. “Daily discharge” means the discharge of a pollutant measured during a calendar day or any 24-hour period that reasonably represents the calendar day for purposes of sampling. For pollutants with limitations expressed in units of mass, the "daily discharge" is calculated as the total mass of the pollutant discharged over the day. For pollutants with limitations expressed in other units of measurement, the "daily discharge" is calculated as the average measurement of the pollutant over the day.
8. “Director” means the Director of the Office of Water, EPA, or an authorized representative.
9. “DMR” means discharge monitoring report.
10. “EPA” means the United States Environmental Protection Agency.
11. “Grab” sample is an individual sample collected over a period of time not exceeding 15 minutes.
12. “IC₂₅” means inhibition concentration 25. The IC₂₅ is a point estimate of the toxicant concentration that would cause a 25% reduction in a nonlethal biological measurement of the test organisms, such as reproduction or growth.
13. “IDEQ” means Idaho Department of Environmental Quality.

REVISED DRAFT

14. "Maximum daily discharge limitation" means the highest allowable "daily discharge."
15. "Method Detection Limit (MDL)" means the minimum concentration of a substance (analyte) that can be measured and reported with 99 percent confidence that the analyte concentration is greater than zero and is determined from analysis of a sample in a given matrix containing the analyte.
16. "QA/QC" means quality assurance/quality control.
17. "QAP" means quality assurance plan.
18. "Regional Administrator" means the Regional Administrator of Region 10 of the EPA, or the authorized representative of the Regional Administrator.
19. "RWC" means receiving water concentration
20. "Severe property damage" means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.
21. "SFCDA" means South Fork Coeur d'Alene.
22. "s.u." means standard unit
23. "TIE" means toxicity identification evaluation.
24. "TRE" means toxicity reduction evaluation
25. "Upset" means an exceptional incident in which there is unintentional and temporary noncompliance with technology-based permit effluent limitations because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, or careless or improper operation.
26. "24-hour composite" sample means a combination of at least 8 discrete sample aliquots of at least 100 milliliters, collected over periodic intervals from the same location, during

REVISED DRAFT

the operating hours of the facility over a 24 hour period. The composite must be flow proportional. The sample aliquots must be collected and stored in accordance with procedures prescribed in the most recent edition of *Standard Methods for the Examination of Water and Wastewater*.